

55 6142

Lightweight cut level F full dip nitrile with sandy foam nitrile palm coated glove

| Gauge | 15gg | | | | | |
|------------|---|--|--|--|--|--|
| Colour | Grey liner / Black coating | | | | | |
| Cuff Style | Knit wrist | | | | | |
| Length | 210-280mm | | | | | |
| Sizes | 5/XXS - 12/3XL | | | | | |
| Packaging | 12 pairs/paper band Sizes 5, 6, 7, 11 & 12 72 pairs/carton Sizes 8, 9 & 10 120 pairs/carton | | | | | |

Features & Benefits

- New RhinoYarn® cut resistant technology
- EN388: 2016+A1:2018 level F cut resistance
- EN407: 2020 contact heat level 1
- Fine 15 gauge lightweight liner
- High level of tactility and dexterity
- A full dip nitrile coating provides liquid and oil repellency,
- whilst the sandy foam palm provides strong grip performance
- Seamless liner and cuff gives a smooth, form-fitting feel
- Touchscreen compatible
- Tested after washing to domestic and industrial wash standards













Performance











Applications / Industries

- Final fix / light assembly
- Automotive assembly
- Light metal fabrication
- Transportation
- Aerospace
- White goods manufacturing











Made with Tilsatec RhinoYarn® technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

Sizing Cuff Colours

| Size | 5 XX-Smal | 6 X-Small | 7 Small | 8 Medium | 9 Large | 10 X-Large | 11 2X-Large | 12 3X-Large |
|-------------------|-----------|-----------|---------|----------|---------|------------|-------------|-------------|
| Colour coded cuff | | | | | | | | |

Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | www.tilsatec.com